



Technical Sheet

On-A-Wall

- P14M
- P8M
- PM

Suggested Specification

Model P14M shall deliver 14.0° gph of 50° F water and 90° F ambient and 80° F inlet water, per ASHRAE 18 Testing. Model P8M shall deliver 8.0 gph of 50° F water and 90° F ambient and 80° F inlet water, per ASHRAE 18 Testing. Cabinet finish shall be greystone powder coated paint on galvanized steel or brushed stainless steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



Models

- P14M delivers 14.0 gph of chilled drinking water
- P8M delivers 8.0 gph of chilled drinking water
- PM is a non-refrigerated fountain.

Standard Features

- Dial-A-Drink® bubbler
- Waterways are Lead-Free in materials & construction
- Stainless steel top
- Welded heavy-gauge steel fram
- High efficiency cooling system

Finishes

- Standard cabinet finish: Greystone powder coated paint on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

Installation

- Prior to roughing consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Options

- Push handle glass fillers (029603-004)
- Kit 029137-002 is required for field installation for the above glass fillers
- VersaFilter

Limited 5-Year Warranty

(Continental limits of the United States and Canada)
Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for “lead free” plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Model	50° F Drinking Water 90° F Ambient Air Temp*			Hot'N Cold™ Model	115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
P14M	14.0	7.8	Yes	No	1/4	4.6	460	Yes	Yes	76 Lbs
P8M	8.0	8.0	No	No	1/4	4.6	4.6	Yes	Yes	72 Lbs
PM	Fountain Only							No	Yes	36 Lbs

*Industry standard rating condition 80° F inlet water temperature

Specifications subject to change without notice

